

**Quality Criteria Verification
Executive Summary
For QCV, Stage Rollout, DMSU and EGI internal**

Name of the component			
Release	emi.blah.sl6.x86_64-1.18.2	RT Ticket	#4850
Software Provider			
Release Contact	Name: Cristina Aiftimiei	E-Mail: cristina.aiftimiei@pd.infn.it	
Validator			
Validator	Name: Esteban Freire García	E-Mail: esfreire@cesga.es	
V. Hours Worked	1		
Component status	Verified	Date	14/01/13
Verification start date	10/01/13	Verification end date	14/01/13

Summary:

emi.blah.sl6.x86_64-1.18.2 was updated from UMD-2 repository and from scratch without any issue.

GGUS Tickets:

Summary of Quality Criteria verification:

	Generic Quality Criteria Total (Critical/Non critical)			
	Passed	Not passed	Not Applicable	Total
TP				
VLD	18			18
Specific Quality Criteria				
TP				
VLD	18			18

Quality Criteria verification cheatsheet:

Criteria	Accepted	Tested	Comments
DOCUMENTATION QC			
GENERIC_DOC_1 (Functional Description)	Optional		
GENERIC_DOC_2 (Release Notes)	Y	VLD	https://rt.egi.eu/rt/Ticket/Display.html?id=4850
GENERIC_DOC_3 (User Documentation)	Y	VLD	https://wiki.italiangrid.it/twiki/bin/view/CREAM/UserGuideEMI2
GENERIC_DOC_4 (Online help (man pages))	Y	VLD	https://wiki.italiangrid.it/twiki/bin/view/CREAM/UserGuideEMI2#Man_pages_for_CREAM_Command_Line
GENERIC_DOC_5 (API Documentation)	Y	VLD	https://wiki.italiangrid.it/twiki/bin/view/CREAM/DevelopersDocumentation
GENERIC_DOC_6 (Administrator Documentation)	Y	VLD	https://wiki.italiangrid.it/twiki/bin/view/CREAM/SystemAdministratorGuideForEMI2
GENERIC_DOC_7 (Service Reference Card)	Y	VLD	https://wiki.italiangrid.it/twiki/bin/view/CREAM/ServiceReferenceCardEMI2
GENERIC_DOC_8 (Software License)	Y	VLD	Emi-cream: Apache Software License 2.0
GENERIC_DOC_9 (Release changes testing)	Y	VLD	https://rt.egi.eu/rt/Ticket/Display.html?id=4850
SOFTWARE DISTRIBUTION QC			
GENERIC_DIST_1 (Source Code Availability)	Y	VLD	
GENERIC_DIST_3 (Binary Distribution)	Y	VLD	http://admin-repo.egi.eu/sw/unverified/umd-2.emi.blah.sl6.x86_64/1/18/2/glite-ce-blahp-1.18.2-3.sl6.x86_64.rpm
SOFTWARE FEATURES QC			
GENERIC_SOFT_1 (Backwards Compatibility)	Y	VLD	
GENERIC_SOFT_2 (New features testing)	Y	VLD	
SERVICE CRITERIA QC			
GENERIC_SERVICE_1 (Service control and status)	Y	VLD	
GENERIC_SERVICE_2 (Log Files)	Y	VLD	
GENERIC_SERVICE_3 (Service Reliability)	Optional		
GENERIC_SERVICE_4 (Service Robustness)	Optional		
GENERIC_SERVICE_5 (Automatic Configuration)	Optional		
GENERIC_SERVICE_6 (Default Password Configuration)	Y	VLD	
SECURITY QC			
GENERIC_SEC_1 (World Writable Files)	Y	VLD	
GENERIC_SEC_3 (Passwords in world readable files)	Y	VLD	
MISCELLANEOUS QC			
GENERIC_MISC_2 (Bug Tracking System)	Y	VLD	GGUS
AUTHENTICATION QC			
AUTHN_IFACE_1 (X.509 Certificate support)	Y	VLD	
AUTHN_DELEG_1 (Delegation Interface)	Y	VLD	
AUTHORISATION QC			
AUTHZ_PCYDEF_3 (Ban User/FQAN)	Y	VLD	
AUTHZ_PCYDEF_4 (Allowed users definition)	Y	VLD	
AUTHZ_PEP_1 (Policy Enforcement)	Y	VLD	
AUTHZ_PEP_2 (User Mapping)	Y	VLD	
JOB EXECUTION QC			
JOBEXEC_IFACE_1 (Job Execution Interface)	Y	VLD	
JOBEXEC_JOB_1 (Simple Job)	Y	VLD	
JOBEXEC_JOB_2 (Simple Job with input/output)	Y	VLD	
JOBEXEC_JOB_3 (Cancel Job)	Y	VLD	
JOBEXEC_EXECMngr_1 (Not Invasive Deployment)	Y	VLD	
JOBEXEC_EXECMngr_2 (Job Management)	Y	VLD	
JOBEXEC_EXECMngr_3 (Information Retrieval)	Y	VLD	
JOBEXEC_AVAIL_1 (Service Redundancy)	Y	VLD	
JOBEXEC_AVAIL_2 (Self Disabling Mechanism)	Optional		
JOBEXEC_AVAIL_4 (Timely Job Status Updates)	Optional		
PARALLEL JOB QC			
PARALLEL_JOB_1 (Simple parallel job submission)	Y	VLD	
PARALLEL_JOB_2 (Single machine parallel job submission)	Optional		
PARALLEL_JOB_3 (Fine grained mapping parallel jobs)	Optional		
MONITORING PROBES QC			
MON_PROBE_GENERIC_1 (Certificate Lifetime)	Optional		
MON_PROBE_GENERIC_2 (Service Probe)	Optional		
MON_PROBE_JOBEXEC_1 (Job Execution Performance)	Y	VLD	

Validator comments:

== EMI.blah.sl6.x86_64-1.18.2 ==

==== Ticket assigned ===

* [https://rt.egi.eu/guest/Ticket/Display.html?id=4850]

(!) Verifier must install a new repo for each product, this information is available at RT ticket field:

{}{}

```
[root@test06 yum.repos.d]# cat EMI.blah.sl6.x86_64.repo
# EGI Software Repository - REPO META (releaseId,repositoryId,repofileId) -
(4850,816,742)
```

```
[EMI.blah.sl6.x86_64]
name=EMI.blah.sl6.x86_64
baseurl=http://admin-repo.egi.eu/sw/unverified/umd-2.emi.blah.sl6.x86_64/1/18/2/
enabled=1
protect=1
priority=1
gpgcheck=1
gpgkey=http://emisoft.web.cern.ch/emisoft/dist/EMI/2/RPM-GPG-KEY-emi
}}}
```

==== Installing ===

* yum update

{}{

```
=====
=====
```

Package Repository	Arch	Version
	Size	

```
=====
=====
```

Updating:

glite-ce-blahp	x86_64	1.18.2-3.sl6
EMI.blah.sl6.x86_64	247 k	

Transaction Summary

```
=====
=====
```

}}}

===== Configure the siteinfo.def file for the CreamCE =====

* This is the site-info used to configure the CreamCE + Torque + MPI

(!)

* Taking the information about how to configure MPI in the CreamCE from the following links:

* <https://wiki.egi.eu/wiki/MAN03>

* There is a point in the previous link pointing to this one, that it is where is explained how to configure YAIM to configure torque + MPI:

<http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtils>

```
{ {{
# YAIM example site configuration file - adapt it to your site!
```

```
#####
# CE configuration variables #
#####
```

```
CE_HOST=test06.egi.cesga.es
WMS_HOST=test22.egi.cesga.es
BDII_HOST=topbdii02.ncg.ingrid.pt
SITE_BDII_HOST=sbdii02.ncg.ingrid.pt
##LFC_HOST=lxb7607.cern.ch
PX_HOST=myproxy.egi.cesga.es
MON_HOST=test07.egi.cesga.es
```

```
YAIM_LOGGING_LEVEL=DEBUG
```

```
#####
# CREAM CE node cluster mode #
#####
CREAMCE_CLUSTER_MODE=no
```

```
#####
# Site configuration variables #
#####
```

```
SITE_EMAIL=egee-admin@cesga.es
```

```
SITE_NAME=CESGA-EGEE
SITE_LOC="Santiago de Compostela, Spain"
SITE_LAT=42.87558      #42.8757 # -90 to 90 degrees
SITE_LONG=-8.553147    #-8.5536 # -180 to 180 degrees
```

```

#####
# Batch server configuration variables #
#####

# Jobmanager specific settings
JOB_MANAGER=lcgpbs
BATCH_SERVER=test06.egi.cesga.es
CE_BATCH_SYS=torque
BATCH_LOG_DIR=/var/torque
BATCH_VERSION=torque-2.5.7-7

#####
# APEL configuration variables #
#####

# Database password for the APEL DB.
APEL_MYSQL_HOST=test07.egi.cesga.es
APEL_DB_PASSWORD=""

#####

# ARGUS authorisation framework control #

#####

# Set USE_ARGUS to yes to enable the configuration of ARGUS

###USE_ARGUS=yes
USE_ARGUS=no

# In case ARGUS is to be used the following should be set
# The ARGUS service PEPD endpoints as a space separated list:

###ARGUS_PEPD_ENDPOINTS="https://test10.egi.cesga.es:8154/authz"
###CREAM_PEPC_RESOURCEID="http://www.egee.cesga.es/test10"

# These variables tell YAIM where to find additional configuration files.
WN_LIST=/opt/glite/yaim/etc/wn-list.conf
USERS_CONF=/opt/glite/yaim/etc/users.conf
GROUPS_CONF=/opt/glite/yaim/etc/groups.conf
FUNCTIONS_DIR=/opt/glite/yaim/functions

#
# SE_dpm-specific settings - Ignore if you are not running a DPM

```

```

#
# Set these if you are installing a DPM yourself
# and/or if you need a default DPM for the lcg-stdout-mon
#
# DPMDATA is now deprecated. Use an entry like $DPM_HOST:/filesystem in
# the DPM_FILESYSTEMS variable.
# From now on we use DPM_DB_USER and DPM_DB_PASSWORD to make clear
# its different role from that of the dpmmgr unix user who owns the
# directories and runs the daemons.

# The name of the DPM head node
DPM_HOST=test08.egi.cesga.es

DPMPOOL=egi-pool * This is the site-info used to configure the CreamCE + Torque +
MPI

(!)

* Taking the information about how to configure MPI in the CreamCE from the
following links:

* https://wiki.egi.eu/wiki/MAN03
* There is a point in the previous link pointing to this one, that it is where is explained
how to configure YAIM to configure torque + MPI:
http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtils
DPM_FILESYSTEMS="$DPM_HOST:/storage"

# The base user
DPM_DB_USER=dpmmgr
DPM_DB_HOST=$DPM_HOST
DPM_DB_PASSWORD=

# Specifies the default amount of space reserved for a file
#DPMFSIZE=200M

DPM_INFO_USER=dpm_info
DPM_INFO_PASS=

# Variable for the port range - Optional, * This is the site-info used to configure the
CreamCE + Torque + MPI

(!)

* Taking the information about how to configure MPI in the CreamCE from the
following links:

* https://wiki.egi.eu/wiki/MAN03
```

* There is a point in the previous link pointing to this one, that it is where is explained how to configure YAIM to configure torque + MPI:
<http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtils> default value is shown
RFIO_PORT_RANGE="20000 25000"

```
# This largely replaces CE_CLOSE_SE but it is a list of hostnames
SE_MOUNT_INFO_LIST="none"
SE_LIST="$DPM_HOST"
SE_ARCH="multidisk" # "disk, tape, multidisk, other"
```

```
#####
# SubCluster configuration #
#####

# Architecture and environment specific settings
CE_CPU_MODEL=Opteron
CE_CPU_VENDOR=amd
CE_CPU_SPEED=2200

CE_OS="ScientificSL" # Forma correcta
CE_OS_RELEASE=5.5
CE_OS_VERSION="Boron"

#New variables
CE_PHYSCPU=2
CE_LOGCPU=2
CE_OS_ARCH=x86_64
CE_CAPABILITY="CPUScalingReferenceSI00=2395"
CE_OTHERDESCR="Cores=24,Benchmark=9.58-HEP-SPEC06"
SE_MOUNT_INFO_LIST="none"
CE_SI00=2395

CE_MINPHYSMEM=524
CE_MINVIRTMEM=512
CE_SMPSIZE=2
CE_SF00=1714
CE_OUTBOUNDIP=TRUE
CE_INBOUNDIP=FALSE * This is the site-info used to configure the CreamCE +
Torque + MPI
```

(!)

* Taking the information about how to configure MPI in the CreamCE from the following links:

* <https://wiki.egi.eu/wiki/MAN03>

- * There is a point in the previous link pointing to this one, that it is where is explained how to configure YAIM to configure torque + MPI:
<http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtils>
CE_RUNTIMEENV=""
LCG-2
LCG-2_1_0
LCG-2_1_1
LCG-2_2_0
LCG-2_3_0
LCG-2_3_1
LCG-2_4_0
LCG-2_5_0
LCG-2_6_0
LCG-2_7_0
GLITE-3_0_0
GLITE-3_0_2
GLITE-3_1_0
R-GMA

"

```
####CREAM CE Variables
CEMON_HOST=test06.egi.cesga.es
CREAM_DB_USER=umdttest
CREAM_DB_PASSWORD="" * This is the site-info used to configure the CreamCE +
Torque + MPI
```

(!)

- * Taking the information about how to configure MPI in the CreamCE from the following links:

- * <https://wiki.egi.eu/wiki/MAN03>
- * There is a point in the previous link pointing to this one, that it is where is explained how to configure YAIM to configure torque + MPI:
<http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtils>
MYSQL_PASSWORD=""
BLPARSER_HOST=test06.egi.cesga.es

```
# MPI CONFIGURATION
#####
MPI_OPENMPI_ENABLE="yes"
MPI_OPENMPI_VERSION="1.4-4"
## If you do NOT provide a shared home, set $MPI_SHARED_HOME to "no" (default).
MPI_SHARED_HOME="no"
## If you do NOT have SSH Hostbased Authentication between your WNs, set the
below variable to "no" (default). Else, set it to "yes".
MPI_SSH_HOST_BASED_AUTH="yes"
### If you use Torque as batch system, you may want to let the yaim plugin configure a
submit filter for you. Uncomment the following line to do so
```

```
MPI_SUBMIT_FILTER="yes"
```

```
# VOS="atlas alice lhcb cms dteam biomed"
# Space separated list of supported VOs by your site
VOS="ops dteam ops.vo.ibergrid.eu iber.vo.ibergrid.eu"
QUEUES="GRID_ops GRID_dteam GRID_opsibeu GRID_iberibeu"
VO_SW_DIR=/opt/exp_soft

#New in Yaim 3.0.1
GRID_OPS_GROUP_ENABLE="ops /VO=ops/GROUP=/ops/ROLE=lcgadmin"
GRID_DTEAM_GROUP_ENABLE="dteam
/VO=dteam/GROUP=/dteam/ROLE=lcgadmin"
GRID_OPSIBEU_GROUP_ENABLE="ops.vo.ibergrid.eu
/VO=ops.vo.ibergrid.eu/GROUP=/ops.vo.ibergrid.eu/ROLE=VO-Admin
/VO=ops.vo.ibergrid.eu/GROUP=/ops.vo.ibergrid.eu/ROLE=Production"
GRID_IBERIBEU_GROUP_ENABLE="iber.vo.ibergrid.eu
/VO=iber.vo.ibergrid.eu/GROUP=/iber.vo.ibergrid.eu/ROLE=VO-Admin /VO=iber.vo.

* This is the site-info used to configure the CreamCE + Torque + MPI
```

(!)

* Taking the information about how to configure MPI in the CreamCE from the following links:

- * <https://wiki.egi.eu/wiki/MAN03>
- * There is a point in the previous link pointing to this one, that it is where is explained how to configure YAIM to configure torque + MPI:
<http://grid.ifca.es/wiki/Middleware/MpiStart/MpiUtilsibergrid.eu/GROUP=/iber.vo.ibergrid.eu/ROLE=Production>"

```
#::::::::::
#ops
#::::::::::
VO_OPS_SW_DIR=$VO_SW_DIR/ops
VO_OPS_DEFAULT_SE=$DPM_HOST
VO_OPS_STORAGE_DIR=$CLASSIC_STORAGE_DIR/ops
VO_OPS_QUEUES="GRID_ops"
VO_OPS_VOMS_SERVERS="vomss://voms.cern.ch:8443/voms/ops?/ops/"
VO_OPS_VOMSES="ops voms.cern.ch 15009
/DC=ch/DC=cern/OU=computers/CN=voms.cern.ch ops"
VO_OPS_VOMS_CA_DN=""DC=ch/DC=cern/CN=CERN Trusted Certification
Authority' '/DC=ch/DC=cern/CN=CERN Trusted Certification Authority""
```

```
#::::::::::
#dteam
#::::::::::
VO_DTEAM_SW_DIR=$VO_SW_DIR/dteam
VO_DTEAM_DEFAULT_SE=$DPM_HOST
VO_DTEAM_STORAGE_DIR=$CLASSIC_STORAGE_DIR/dteam
```

```
VO_DTEAM_QUEUES="GRID_dteam"
VO_DTEAM_VOMS_SERVERS='vomss://voms.hellasgrid.gr:8443/voms/dteam?/dteam'
VO_DTEAM_VOMSES=""dteam lcg-voms.cern.ch 15004
/DC=ch/DC=cern/OU=computers/CN=lcg-voms.cern.ch dteam 24' 'dteam voms.cern.ch
15004 /DC=ch/DC=cern/OU=computers/CN=voms.cern.ch dteam 24' 'dteam
voms.hellasgrid.gr 15004 /C=GR/O=HellasGrid/
OU=hellasgrid.gr/CN=voms.hellasgrid.gr dteam 24' 'dteam voms2.hellasgrid.gr
15004 /C=GR/O=HellasGrid/OU=hellasgrid.gr/CN=voms2.hellasgrid.gr dteam 24"
VO_DTEAM_VOMS_CA_DN=""'/DC=ch/DC=cern/CN=CERN Trusted Certification
Authority' '/DC=ch/DC=cern/CN=CERN Trusted Certification Authority'
'/C=GR/O=HellasGrid/OU=Certification Authorities/CN=HellasGrid CA 2006'
'/C=GR/O=HellasGrid/OU=Certif
ication Authorities/CN=HellasGrid CA 2006""
```

```
## IBERGRID VOS ##
# ops.vo.ibergrid.eu
VO_OPS_VO_IBERGRID_EU_SW_DIR=$VO_SW_DIR/opsibeu
VO_OPS_VO_IBERGRID_EU_DEFAULT_SE=$DPM_HOST
VO_OPS_VO_IBERGRID_EU_STORAGE_DIR=$CLASSIC_STORAGE_DIR/opsib
eu
VO_OPS_VO_IBERGRID_EU_QUEUES="GRID_opsibeu"https://test06.egi.cesga.es:
8443/CREAM578415886
VO_OPS_VO_IBERGRID_EU_VOMS_SERVERS=""vomss://voms02.ncg.ingrid.pt:84
43/voms/ops.vo.ibergrid.eu?/ops.vo.ibergrid.eu"""
VO_OPS_VO_IBERGRID_EU_VOMSES=""ops.vo.ibergrid.eu voms02.ncg.ingrid.pt
40001 /C=PT/O=LIPCA/O=LIP/OU=Lisboa/CN=voms02.ncg.ingrid.pt
ops.vo.ibergrid.eu"""
VO_OPS_VO_IBERGRID_EU_VOMS_CA_DN=""'/C=PT/O=LIPCA/CN=LIP
Certification Authority""
```

```
# iber.vo.ibergrid.eu
VO_IBER_VO_IBERGRID_EU_SW_DIR=$VO_SW_DIR/iberibeu
VO_IBER_VO_IBERGRID_EU_DEFAULT_SE=$DPM_HOST
VO_IBER_VO_IBERGRID_EU_STORAGE_DIR=$CLASSIC_STORAGE_DIR/iberi
beu
VO_IBER_VO_IBERGRID_EU_QUEUES="GRID_iberibeu"
VO_IBER_VO_IBERGRID_EU_VOMS_SERVERS=""vomss://voms02.ncg.ingrid.pt:8
443/voms/iber.vo.ibergrid.eu?/iber.vo.ibergrid.eu"""
VO_IBER_VO_IBERGRID_EU_VOMSES=""iber.vo.ibergrid.eu voms02.ncg.ingrid.pt
40003 /C=PT/O=LIPCA/O=LIP/OU=Lisboa/CN=voms02.ncg.ingrid.pt
iber.vo.ibergrid.eu"""
VO_IBER_VO_IBERGRID_EU_VOMS_CA_DN=""'/C=PT/O=LIPCA/CN=LIP
Certification Authority"""
}}}
```

```
{{{  
ops.vo.ibergrid.eu and iber.vo.ibergrid.eu VOs were included from verification VOMS  
server installed at LIP. (voms02.ncg.ingrid.pt)
```

LB and WMS were configured at IFIC (tst04.ific.uv.es & tst05.ific.uv.es)

TopBDII was configured for verification in topbdii02.ncg.ingrid.pt.

<https://test06.egi.cesga.es:8443/CREAM578415886>

}}}

* Set your siteinfo.def file, which is the input file used by yaim. Documentation about yaim variables relevant for CREAM CE is available at:

* [https://twiki.cern.ch/twiki/bin/view/LCG/Site-configuration_variables#cream_CE]

-->quedei aqui

(!) Be sure that CREAMCE_CLUSTER_MODE is set to no (or not set at all).

(!) The MPI_CE profile should be the first in the yaim configuration, otherwise the Glue variables will not be properly defined. This restriction may be removed in future versions.

===== Configuring with YAIM the CreamCE =====

```
{{{  
/opt/glite/yaim/bin/yaim -c -s /opt/glite/yaim/etc/site-info.def -n MPI_CE -n creamCE  
-n TORQUE_server -n TORQUE_utils  
[ .... ]
```

Starting glite-lb-interlogd ... done

INFO: Executing function: config_cream_glite_initd

INFO: Executing function: config_torque_server_setenv

INFO: Currently this function doesn't set any environment variables.

INFO: Executing function: config_torque_server

INFO: Re-starting the torque server

pbs_server is not running.

/var/torque/server_priv/serverdb

Starting TORQUE Server: [OK]ation: [OK]

Max open servers: 9

create queue GRID_ops

Max open servers: 9

create queue GRID_dteam

Max open servers: 9

create queue GRID_opsibeu

Max open servers: 9

create queue GRID_iberibeu

Max open servers: 9

set server scheduling = True

set server acl_host_enable = False

set server managers = root@test06.egi.cesga.es

```
set server operators = root@test06.evi.cesga.es
set server default_queue = dteam
set server log_events = 511
set server mail_from = adm
set server mail_domain = never
set server query_other_jobs = True
set server scheduler_iteration = 600
set server default_node = lcgpro
set server node_pack = False
set server kill_delay = 10
set server authorized_users = *@test06.evi.cesga.es
Max open servers: 9
set queue GRID_ops queue_type = Execution
set queue GRID_ops resources_max.cput = 48:00:00
set queue GRID_ops resources_max.walltime = 72:00:00
set queue GRID_ops enabled = True
set queue GRID_ops started = True
set queue GRID_ops acl_group_enable = True
Max open servers: 9
set queue GRID_dteam queue_type = Execution
set queue GRID_dteam resources_max.cput = 48:00:00
set queue GRID_dteam resources_max.walltime = 72:00:00
set queue GRID_dteam enabled = True
set queue GRID_dteam started = True
set queue GRID_dteam acl_group_enable = True
Max open servers: 9
set queue GRID_opsibeu queue_type = Execution
set queue GRID_opsibeu resources_max.cput = 48:00:00
set queue GRID_opsibeu resources_max.walltime = 72:00:00
set queue GRID_opsibeu enabled = True
set queue GRID_opsibeu started = True
set queue GRID_opsibeu acl_group_enable = True
Max open servers: 9
set queue GRID_iberibeu queue_type = Execution
set queue GRID_iberibeu resources_max.cput = 48:00:00
set queue GRID_iberibeu resources_max.walltime = 72:00:00
set queue GRID_iberibeu enabled = True
set queue GRID_iberibeu started = True
set queue GRID_iberibeu acl_group_enable = True
Shutting down TORQUE Server: [ OK ]
/var/torque/server_priv/serverdb
Starting TORQUE Server: [ OK ]
    INFO: Executing function: config_maui_cfg_setenv
    INFO: Executing function: config_maui_cfg
    INFO: configuring maui ...
MPI_CE creamCE TORQUE_server TORQUE_utils
MAUI is already stopped: [ OK ]
Starting MAUI Scheduler: [ OK ]
    INFO: Executing function: config_apel_pbs_setenv
    INFO: Executing function: config_apel_pbs
```

```
INFO: Executing function: config_gip_sched_plugin_pbs_setenv
INFO: Executing function: config_gip_sched_plugin_pbs
INFO: Executing function: config_torque_submitter_ssh
WARNING: The munge key /etc/munge/munge.key does not exist.
WARNING: Munge is required to submit jobs to the torque server.
WARNING: Not starting the munge daemon
Reloading sshd: [ OK ]
INFO: Configuration Complete. [ OK ]
INFO: YAIM terminated successfully.
[root@test06 etc]#
```

```
}}}
```

```
==== TESTING ====
```

```
===== Checking ldap (OK) =====
```

```
{{{
```

```
[root@ce2 etc]# ldapsearch -x -H ldap://sbdii02.ncg.ingrid.pt:2170 -b o=grid | grep cesga
```

```
# test06.egi.cesga.es, UMD-VERIFICATION, grid
```

```
dn: GlueClusterUniqueID=test06.egi.cesga.es,Mds-Vo-name=UMD-VERIFICATION,o=gri
```

```
GlueClusterUniqueID: test06.egi.cesga.es
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_ops
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_dteam
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_opsibergrid
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_iebergrid
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_ops
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_dteam
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_opsibe
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_iebergr
```

```
GlueClusterName: test06.egi.cesga.es
```

```
}}}
```

```
{{{
```

```
[root@ce2 etc]# ldapsearch -x -H ldap://topbdii02.ncg.ingrid.pt:2170 -b o=grid | grep test06
```

```
# test06.egi.cesga.es, UMD-VERIFICATION, local, grid
```

```
dn: GlueClusterUniqueID=test06.egi.cesga.es,Mds-Vo-name=UMD-VERIFICATION,Mds-V
```

```
GlueClusterUniqueID: test06.egi.cesga.es
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_ops
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_dteam
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_opsibergrid
```

```
GlueClusterService: test06.egi.cesga.es:8443/cream-pbs-GRID_ibergrid
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_ops
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_dteam
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_opsibe
```

```
GlueForeignKey: GlueCEUniqueID: test06.egi.cesga.es:8443/cream-pbs-GRID_ibergr
```

```
GlueClusterName: test06.egi.cesga.es
```

```
}}}
```

```
{{{
```

```
[root@ce2 etc]# ldapsearch -x -H ldap://test06.egi.cesga.es:2170 -b o=grid | grep
```

```
GlueCEStateFreeCPUs
```

```
GlueCEStateFreeCPUs: 4
```

```
GlueCEStateFreeCPUs: 4
```

```
GlueCEStateFreeCPUs: 4
```

```
GlueCEStateFreeCPUs: 4
```

```
}}}
```

```
{{{
```

```
[root@ce2 common]# ldapsearch -x -h test06.egi.cesga.es -p 2170 -b mds-vo-name=resource,o=grid | grep MPI
```

```
GlueHostApplicationSoftwareRunTimeEnvironment: MPI-START  
GlueHostApplicationSoftwareRunTimeEnvironment: MPI_NO_SHARED_HOME  
GlueHostApplicationSoftwareRunTimeEnvironment: OPENMPI  
GlueHostApplicationSoftwareRunTimeEnvironment: OPENMPI-1.4-4
```

```
}}}
```

```
{{{  
[root@se2 tmp]# ldapsearch -x -h test06.egi.cesga.es -p 2170 -b mds-vo-  
name=resource,o=grid | grep 444  
GlueCEStateWaitingJobs: 444444  
}}}
```

* Checking if MPI has been configured correctly

```
{{{  
[root@test06 etc]# cat /var/torque/torque.cfg  
SUBMITFILTER /var/torque/submit_filter  
}}}
```

==== Checking if ssh works in bidirectional sense ====

* From WN to CE (OK)

```
{{{
```

```
[root@test14 ~]# su - dteam004  
[dteam004@test14 ~]$ ssh test06.egi.cesga.es  
[dteam004@test06 ~]$
```

```
}}}
```

==== Trying some internal commands ====

}}} {

[root@test06 etc]# qstat -B

Server	Max	Tot	Que	Run	Hld	Wat	Trn	Ext	Status
test06.egi.cesga	0	0	0	0	0	0	0	0	Active

[root@test06 etc]# qstat -Q

Queue	Max	Tot	Ena	Str	Que	Run	Hld	Wat	Trn	Ext	T
GRID_ops	0	0	yes	yes	0	0	0	0	0	0	E
GRID_dteam	0	0	yes	yes	0	0	0	0	0	0	E
GRID_opsibeu	0	0	yes	yes	0	0	0	0	0	0	E
GRID_iberibeu	0	0	yes	yes	0	0	0	0	0	0	E

}}}

* Checking the environment on the WNs

}}} {
[dteam004@test14 ~]\$ env|grep MPI_
MPI_OPENMPI_PATH=/usr/lib64/openmpi/1.4-gcc
MPI_OPENMPI_VERSION=1.4
MPI_DEFAULT_FLAVOUR=openmpi
I2G_MPI_START=/usr/bin/mpi-start

}}}

* Submitting a direct qsub

}}} {

[opssgm004@test06 ~]\$ vi test.sh
[opssgm004@test06 ~]\$ chmod +x test.sh
[opssgm004@test06 ~]\$ qsub -q GRID_ops -l nodes=test14.egi.cesga.es test.sh
0.test06.egi.cesga.es
[opssgm004@test06 ~]\$ ls
test.sh test.sh.e0 test.sh.o0
[opssgm004@test06 ~]\$ cat test.sh.e0
[opssgm004@test06 ~]\$ cat test.sh.o0
test14.egi.cesga.es
Thu Jan 10 17:12:24 CET 2013

}}}

(!)

==== Submitting a job from the CESGA UI ====

{{{

```
[esfreire@test13 ~]$ glite-ce-delegate-proxy -e test06.egi.cesga.es esfreire
2013-01-10 17:16:39,606 NOTICE - Proxy with delegation id [esfreire] successfully
delegated to endpoint [https://test06.egi.cesga.es:8443//ce-cream/services/gridsite-
delegation]
```

```
[esfreire@test13 ~]$ glite-ce-proxy-renew -e test06.egi.cesga.es esfreire
2013-01-10 17:17:51,075 NOTICE - Proxy with delegation id [esfreire] successfully
renewed to endpoint [https://test06.egi.cesga.es:8443//ce-cream/services/gridsite-
delegation]
```

}}}

{{{

{{{

```
[esfreire@test13 ~]$ glite-ce-job-submit -D esfreire -r test06.egi.cesga.es:8443/cream-
pbs-GRID_ops testCream1.jdl
https://test06.egi.cesga.es:8443/CREAM976905590
```

```
[esfreire@test13 ~]$ glite-ce-job-status
https://test06.egi.cesga.es:8443/CREAM976905590
```

```
***** JobID=[https://test06.egi.cesga.es:8443/CREAM976905590]
      Status      =[DONE-OK]
      ExitCode    =[0]
```

}}}

==== Submitting MPI jobs ====

{{{

```
[esfreire@test13 verification]$ cat job1.jdl
CPUNumber = 4;
Executable = "/usr/bin/mpi-start";
Arguments = "-v -pre hooks.sh cpi";
InputSandbox = {"cpi.c", "hooks.sh"};
StdOutput = "std.out";
StdError = "std.err";
OutputSandbox = {"std.out", "std.err"};
##OutputSandboxBaseDestUri = "gsiftp://localhost";
OutputSandboxBaseDestUri = "gsiftp://se2.egi.cesga.es/tmp";
```

```

Requirements =
  Member("MPI-START", other.GlueHostApplicationSoftwareRunTimeEnvironment)
  &&
  Member("OPENMPI", other.GlueHostApplicationSoftwareRunTimeEnvironment);
} }

{{{
[esfreire@test13 verification]$ cat cat hooks.sh
#!/bin/sh

pre_run_hook () {

# Compile the program.
echo "Compiling ${I2G_MPI_APPLICATION}"

sleep 20

# Actually compile the program.
cmd="mpicc ${MPI_MPICC_OPTS} -o ${I2G_MPI_APPLICATION} ${I2G_MPI_APPLICATION}.c"
$cmd
if [ ! $? -eq 0 ]; then
  echo "Error compiling program. Exiting..."
  return 1
fi

# Everything's OK.
echo "Successfully compiled ${I2G_MPI_APPLICATION}"

return 0
}

}}}

[esfreire@test13 verification]$ cat job2.jdl
CPUNumber = 2;
Executable = "/usr/bin/mpi-start";
Arguments = "-t openmpi -v -pre hooks.sh cpi";
InputSandbox = {"cpi.c", "hooks.sh"};
StdOutput = "std.out";
StdError = "std.err";
OutputSandbox = {"std.out", "std.err"};
OutputSandboxBaseDestUri = "gsiftp://se2.egi.cesga.es/tmp";
Requirements =
  Member("MPI-START", other.GlueHostApplicationSoftwareRunTimeEnvironment)
  &&
  Member("OPENMPI", other.GlueHostApplicationSoftwareRunTimeEnvironment);
}

```

```
[esfreire@test13 verification]$ glite-ce-job-status  
https://test06.egi.cesga.es:8443/CREAM942629962  
  
***** JobID=[https://test06.egi.cesga.es:8443/CREAM942629962]  
Status      = [DONE-OK]  
ExitCode    = [0]  
  
}}}  
  
{ {{  
[root@se2 tmp]# cat std.err  
mpi-start [INFO ]:  
*****  
mpi-start [INFO ]: UID   = opssgm006  
mpi-start [INFO ]: HOST  = test15.egi.cesga.es  
mpi-start [INFO ]: DATE  = Thu Jan 10 18:17:55 CET 2013  
mpi-start [INFO ]: VERSION = 1.1.0  
mpi-start [INFO ]:  
*****  
mpi-start [INFO ]: search for scheduler  
mpi-start [INFO ]: activate support for pbs  
mpi-start [INFO ]: Unable to detect number of cores per cpu, assuming 1  
mpi-start [INFO ]: Detected 0 CPU socket(s) and 1 core(s) per CPU  
mpi-start [INFO ]: activate support for openmpi  
mpi-start [INFO ]: call backend MPI implementation  
mpi-start [INFO ]: start program with mpirun  
Process 0 on test15.egi.cesga.es: n=1  
Using 16384 intervals  
Process 1 on test15.egi.cesga.es: n=1
```

```
[root@se2 tmp]# cat std.out  
Compiling cpi  
Successfully compiled cpi  
=[START]==  
=====  
pi is approximately 3.1415926539002363, Error is 0.0000000003104432  
wall clock time = 0.001998  
=[FINISHED]==  
=====
```

```
}}}  
  
{ {{  
[esfreire@test13 verification]$ cat job3.jdl  
NodeNumber = 2;  
SMPGranularity = 2;
```

```

WholeNodes    = True;
Executable    = "/usr/bin/mpi-start";
Arguments     = "-v -pre hooks.sh cpi";
InputSandbox  = {"cpi.c", "hooks.sh"};
StdOutput     = "std.out";
StdError      = "std.err";
OutputSandbox = {"std.out", "std.err"};
OutputSandboxBaseDestUri = "gsiftp://se2.egi.cesga.es/tmp";
Requirements =
    Member("MPI-START", other.GlueHostApplicationSoftwareRunTimeEnvironment)
&&
    Member("OPENMPI", other.GlueHostApplicationSoftwareRunTimeEnvironment);

```

```
[esfreire@test13 verification]$ glite-ce-job-submit -r test06.egi.cesga.es:8443/cream-
pbs-GRID_ops -D esfreire job3.jdl
https://test06.egi.cesga.es:8443/CREAM342252956
```

```
}}}
```

```
{{{
```

```
[root@se2 tmp]# cat std.err
mpi-start [INFO ]:
*****
mpi-start [INFO ]: UID   = opssgm006
mpi-start [INFO ]: HOST  = test15.egi.cesga.es
mpi-start [INFO ]: DATE  = Tue Jan 17 18:27:14 CET 2012
mpi-start [INFO ]: VERSION = 1.1.0
mpi-start [INFO ]:
*****
mpi-start [INFO ]: search for scheduler
mpi-start [INFO ]: activate support for pbs
mpi-start [INFO ]: Unable to detect number of cores per cpu, assuming 1
mpi-start [INFO ]: Detected 0 CPU socket(s) and 1 core(s) per CPU
mpi-start [INFO ]: activate support for openmpi
mpi-start [INFO ]: call backend MPI implementation
mpi-start [INFO ]: start program with mpirun
Process 0 on test15.egi.cesga.es: n=1
Using 16384 intervals
Process 1 on test15.egi.cesga.es: n=1
[root@se2 tmp]# cat std.out
Compiling cpi
Successfully compiled cpi
=[START]==
=====
pi is approximately 3.1415926539002363, Error is 0.0000000003104432
wall clock time = 0.001926
=[FINISHED]==
=====
}}}
```

```

{{{
[esfreire@test13 verification]$ cat job-oldsyntax.jdl
CPUNumber = 4;
Executable = "starter.sh";
Arguments = "cpi OPENMPI";
InputSandbox = {"starter.sh", "cpi.c", "hooks.sh"};
StdOutput = "std.out";
StdError = "std.err";
OutputSandbox = {"std.out", "std.err"};
OutputSandboxBaseDestUri = "gsiftp://se2.egee.cesga.es/tmp";
Environment = {"I2G_MPI_PRE_RUN_HOOK=hooks.sh"};
Requirements =
    Member("MPI-START", other.GlueHostApplicationSoftwareRunTimeEnvironment)
&&
    Member("OPENMPI", other.GlueHostApplicationSoftwareRunTimeEnvironment);

}}}

```

```

[root@se2 tmp]# cat std.err
mpi-start [INFO ]:
*****
mpi-start [INFO ]: UID    = opssgm006
mpi-start [INFO ]: HOST   = test15.evi.cesga.es
mpi-start [INFO ]: DATE   = Wed Jan 25 09:50:04 CET 2012
mpi-start [INFO ]: VERSION = 1.1.0
mpi-start [INFO ]:
*****
mpi-start [INFO ]: search for scheduler
mpi-start [INFO ]: activate support for pbs
mpi-start [INFO ]: Unable to detect number of cores per cpu, assuming 1
mpi-start [INFO ]: Detected 0 CPU socket(s) and 1 core(s) per CPU
mpi-start [INFO ]: activate support for openmpi
mpi-start [INFO ]: call backend MPI implementation
mpi-start [INFO ]: start program with mpirun
Process 0 on test15.evi.cesga.es: n=1
Using 16384 intervals
Process 2 on test14.evi.cesga.es: n=1
Process 3 on test14.evi.cesga.es: n=1
Process 1 on test15.evi.cesga.es: n=1

```

```

[root@se2 tmp]# cat std.out
Compiling cpi
Successfully compiled cpi
=[START]=====
=====
pi is approximately 3.1415926539002341, Error is 0.0000000003104410
wall clock time = 0.003777

```

==[FINISHED]=====

}}}

Not applicable Quality Criteria

Specific Functional Tests to be repeated in SR:

Test number	Description	Motivation

Specific Non-functional tests (Scalability, etc...) to be repeated in SR:

Test number	Description	Motivation

Comments for UMD QC definition (TSA2.2):

- Review criteria xxxx
- Add criteria xxxx

Comments for SR (TSA1.3):

emi.blah.sl6.x86_64-1.18.2 was updated from UMD-2 repository and from scratch without any issue.

Comments for DMSU (TSA2.5):

Comments for TP: